



YU KUNYU

BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM



仲賢行有限公司
CYH Limited

寫字樓 : 香港九龍尖沙咀東部加連威老道100號港晶中心9樓911室
電話 : (852) 2967 3999 傳真 : (852) 2818 6890
旺角鋪門市 : 九龍旺角上海街687號地下 電話 : (852) 2390 2188
荃灣鋪門市 : 新界荃灣德華街18號德範樓地下 電話 : (852) 2882 8281



YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

About Wuan City Kun Yu Metal Products Co., Ltd

Wuan City Kun Yu Metal Products Co., Ltd. Is a professional manufacturer of cast-iron drainage pipes and sets up in 2006, the enterprise covers a total area of 70,000 square meters, with an annual output of 20,000 tons of cast-iron drainage pipes and 10,000 tons of cast-iron pipe fittings.

Kun Yu factory has advanced production equipment and complete testing methods. The whole process is controlled strictly by inspection, so that the products can meet the standard requirements in chemical composition, mechanical properties, organization, hydraulic test, and other aspects, providing a reliable guarantee for the excellent quality of the products. The company adheres to the quality policy of sustainable development to create a green factory, in which "Quality is the basis of reputation, Technology, and Management are the basis of efficiency." and conscientiously implements the ISO9001 quality management system standards. The product quality has reached the advanced level of ISO6594, BS EN877, ASTMA888, GB/T12772, KSD4307, and multinational advanced level, exported to Hong Kong, United Kingdom, Germany, Russia, Norway, Sweden, and other regions.

At present, the main products of the Kun Yu factory are cast iron pipes and fittings. The drainage cast iron pipes are produced by centrifugal casting with the hot mold method, special internal and external surface treatment, epoxy resin anti-corrosion coating, high-temperature drying coating, and other advanced technologies.

The company has 15 centrifuge casting machines, 2 shot blasting machines, 2 sets of automatic cutting internal grinding machines, 7 sets of pipe grinding machines, more than 1500 kinds of pipe fitting molds, and a set of automatic horizontal production lines.

Quality testing equipment: tensile test machine, hardness test machine, carbon, and sulfur analyzer, and two sets of cold and hot water circulation equipment. The product has the characteristic of high strength and lightweight, and the installation is very convenient, thus can greatly accelerate the construction schedule; The product has a thin wall, uniform, smooth inside and outside; Dense structure, no leakage, corrosion resistance, anti-seismic, anti-noise, high-temperature resistance, simple construction and maintenance, reliable installation, long durability, and other advantages.

Wuan City Kun Yu Metal Products Co., Ltd. always adheres to the "sincere to the world's customers, cast a global quality pipe" business purpose, dedicated to service and cooperating with domestic and foreign merchants.



YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

關於武安市坤鈺屬製品有限公司

武安市坤鈺金屬製品有限公司，是專業生產鑄鐵排水管的企業。企業 2006 年建廠，總佔地面積 70,000 平方米，年產量鑄鐵排水管 20,000 噸、鑄鐵管件 10,000 噸，目前公司已擁有一批高技術、高素質、高服務的精銳團隊。

廠生產設備先進，檢測方法齊全。通過檢測進行嚴格的工序控制，使產品在化學成分、機械性能、水壓試驗等各方面均達到標準要求，為出廠產品的優良質量提供了可靠的保證。公司堅持“質量是信譽之基，技術和管理是效益之本。”的持續發展的質量方針，認真貫徹 ISO9001 質量管理體系標準之基、創建綠色工廠。產品質量均達到 ISO6594、BS EN877、ASTMA888、GB/T12772、KSD4307 等多國先進水平，出口香港、英國、德國、俄羅斯、挪威、瑞典等地區


目前廠的經營產品主要為鑄鐵管和鑄鐵管件，生產的排水鑄鐵管採用了離心鑄造特殊的內外表面處理，環氧樹脂防腐層、高溫烘乾塗裝等先進工藝。公司現有離心機 15 台，拋丸機 2 台、自動切割內磨機 2 套，磨管機 7 台，管件模具達到 1500 多種，一整套自動水平生產線，質量檢測設備：光譜分析儀、耐鹽霧試驗機、測試拉力實驗機、硬度實驗機、碳硫分析儀，冷熱水循環設備兩套。產品具有強度高重量輕的特點，安裝極為方便，因而可以大大加快施工進度；該產品具有壁薄、均勻、內外光滑；組織緻密，無滲漏、耐腐蝕、抗震、防噪音、耐高溫，施工及維護簡便，安裝可靠，耐久性長等優點。





YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

Manufacturing and Inspection Procedure





YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

Advantages of Product

低噪音 Superior Noise Suppression

不易燃 Fire Resistance

耐用 Longevity

容易安裝 Easy to Assemble, Install.

不易變形 Low Thermal Expansion Rates



Certificates





YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


PIPE

Nominal Size (mm)	Size (Inch)	Outside Diameter D(mm)	Wall thickness T (mm)		Length (mm)
			Nominal Value	Minimum Value	
40	1-1/2"	48	3.00	2.50	3,000
50	2"	58	3.50	3.00	
75	3"	83	3.50	3.00	
100	4"	110	3.50	3.00	
150	6"	160	4.00	3.50	
200	8"	210	5.00	4.00	
250	10"	274	5.50	4.50	
300	12"	326	6.00	5.00	



Body Marking:

YU KUNYU SML BSEN877 A2-s1, d0 (DN) x (Length)






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

Fitting


15° BEND

Nominal Size(mm)	kg/pcs.	H (mm)
50	0.5	35
75	0.8	45
100	1.1	50
150	2.5	65




22° BEND

Nominal Size(mm)	kg/pcs.	H (mm)
50	0.5	45
100	1.3	54
150	3.2	70




30° BEND

Nominal Size(mm)	kg/pcs.	H (mm)
50	0.5	45
75	0.8	60
100	1.3	60
150	3.0	80
200	5.6	95




45° BEND

Nominal Size(mm)	kg/pcs.	H (mm)
50	0.5	50
75	1.0	60
100	1.5	70
150	3.5	90
200	6.3	110
250	10.3	130
300	17.3	155



88° BEND

Nominal Size(mm)	kg/pcs.	H (mm)
50	0.7	75
75	1.0	95
100	1.5	110
150	3.5	145
200	6.3	180
250	10.7	222
300	17.3	263






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


45° BEND WITH ACCESS DOOR

Nominal Size(mm)	kg/pcs.	H (mm)
50	1.0	60
75	1.7	76
100	2.6	83
150	7.0	113
200	9.0	124
250	20.4	162
300	39.8	207




88° BEND WITH ACCESS DOOR

Nominal Size(mm)	kg/pcs.	H (mm)
50	1.1	76
75	2.2	95
100	3.4	110
150	7.0	150
200	13.5	182
250	26.3	222
300	33.5	263




88° DOUBLE ACCESS BEND

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	L (mm)
50	1.2	20	121	100
75	1.8	60	145	120
100	3.2	70	170	140
150	7.0	90	219	180




88° VENT BEND

Nominal Size(mm)	kg/pcs.	H (mm)	L (mm)
100 x 50	2.5	111	111



88° LONG RADIUS BEND

Nominal Size(mm)	kg/pcs.	H (mm)	R (mm)
75	3.6	288	250
100	5.4	272	230
100	7.5	434	400
150	9.8	277	230
150	19.5	635	600
200	19.5	350	300
200	23	460	400






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


88° LONG RADIUS BEND ACCESS DOOR

Nominal Size(mm)	kg/pcs.	H (mm)	R (mm)
100	7	252	150
100	9.5	479	450
150	21.5	635	600
200	23	446	400
200	35	645	600
250	49	558	500
250	51	655	600
300	75	666	600




88° TOP-SOCKET BEND

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	L (mm)
100 x 50	2.5	203	110	110




45° CROSS TEE

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	L (mm)
100 x 50	2.7	204	167	167
100 x 100	5.3	263	192	192
150 x 100	9.0	298	242	242
150 x 150	10.8	358	269	269




88° CROSS TEE

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	H2 (mm)	L (mm)
100x50	2.2	183	81	102	107
100x100	3.4	345	167	178	122
150x100	7.1	400	192	208	147



88° ELBOW TEE

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	H2 (mm)	L (mm)
100 x 100	3.4	220	105	115	120
150 x 100	7.1	245	115	130	145






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


45° SINGLE BRANCH

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	H2 (mm)	L (mm)
50 x 50	1.4	188	137	51	137
75 x 50	1.8	192	141	51	141
75 x 75	2.4	228	162	66	162
100 x 50	2.5	204	167	37	167
100 x 75	3.1	233	182	51	182
100 x 100	4.2	278	208	70	208
150 x 50	5.5	283	242	41	242
150 x 75	5.9	258	218	40	218
150 x 100	6.8	299	243	56	243
150 x 150	9.2	359	268	91	268
200 x 75	8.3	262	242	20	242
200 x 100	10.0	307	267	40	267
200 x 150	13.3	379	303	76	303
200 x 200	17.2	460	343	117	343
250 x 100	15.4	328	313	15	313
250 x 150	20.2	409	353	56	353
250 x 200	25.1	480	389	91	389
250 x 250	31.5	566	434	132	434
300 x 150	26.9	419	384	35	384
300 x 200	34.0	485	415	70	440
300 x 300	48.2	667	510	157	510



45° INSPECTION BRANCH

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	H2 (mm)	L (mm)
75 x 75	3.0	229	163	66	163
100 x 50	3.6	214	173	41	158
100 x 75	4.5	264	197	67	200
100 x 100	5.3	275	205	70	206
150 x 100	8.0	285	238	47	230
150 x 150	10.4	356	268	88	267
200 x 100	11.0	346	306	40	304
200 x 150	14.0	395	340	55	389
200 x 200	16.4	488	376	112	370
250 x 250	40.0	588	453	135	452
300 x 300	57.2	694	538	156	528






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


88° SINGLE BRANCH

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	H2 (mm)	L (mm)
50 x 50	0.9	146	66	80	81
75 x 50	1.6	155	85	90	91
75 x 75	1.9	183	87	96	95
100 x 50	2.1	174	78	96	107
100 x 75	2.6	193	87	106	112
100 x 100	2.9	223	107	116	122
150 x 50	4.4	203	108	95	142
150 x 75	5.0	223	106	117	142
150 x 100	5.5	247	131	116	146
150 x 150	6.9	302	159	143	156
200 x 100	7.8	271	142	129	175
200 x 150	10.8	329	175	154	154
200 x 200	12.8	379	182	197	190
250 x 100	14.0	311	162	149	148
250 x 150	15.0	359	171	188	189
250 x 200	17.5	408	197	211	235
250 x 250	27.0	473	230	243	246
300 x 100	22.0	348	184	164	185
300 x 150	22.8	404	192	212	258
300 x 200	27.0	455	220	235	265
300 x 250	31.6	525	273	252	279
300 x 300	35.0	554	282	272	278



88° INSPECTION BRANCH

Nominal Size(mm)	kg/pcs	H (mm)	H1 (mm)	H2 (mm)	L (mm)
50 x 50	1.3	146	66	80	81
75 x 50	5.0	183	87	96	91
75 x 75	2.9	222	91	131	131
100 x 50	3.8	205	100	105	96
100 x 75	3.8	204	92	112	112
100 x 100	4.5	276	105	171	153
150 x 100	7.5	278	115	163	165
150 x 150	11.0	353	148	205	192
200 x 100	10.5	313	146	167	177
200 x 150	11.6	343	166	177	187
200 x 200	14.3	379	182	197	204
250 x 150	34.6	440	213	227	226
250 x 200	26.5	448	217	231	235
250 x 250	31.0	473	230	243	246
300 x 200	33.6	465	225	240	265
300 x 300	43.5	549	266	283	283






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


STACK SUPPORT PIPE

Nominal Size(mm)	kg/pcs.	H (mm)	L (mm)
50	1.3	200	87
75	1.6	220	118
100	2.3	200	145
150	4.0	200	195
200	6.0	200	245
250	12.5	300	340
300	24.0	350	430



REDUCER (ECCENTRIC)

Nominal Size(mm)	kg/pcs.	H (mm)	L (mm)
75 x 50	0.5	80	13
100 x 50	0.9	80	25
100 x 75	1.1	90	14
150 x 50	2.0	103	51
150 x 75	2.2	101	39
150 x 100	2.2	106	25
200 x 100	4.1	116	50
200 x 150	4.3	126	25
250 x 100	6.2	128	82
250 x 150	6.8	132	57
250 x 200	7.0	146	32
300 x 150	10.7	152	84
300 x 200	11.4	162	59
300 x 250	12.4	170	26



Short pipe with Square Door

Nominal Size(mm)	kg/pcs.	H (mm)	L (mm)
200	22	110	465
250	35	150	570
300	51	190	640






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


ANTI-SIPHON TRAP WITH DOOR

Nominal Size(mm)	kg/pcs.	H (mm)	H1 (mm)	L (mm)
50	3	260	80	180
75	7	305	86	230
100	12	380	85	320
150	35	620	85	470
200	54	742	85	503




Anti-Syphonage Trap with Water Seal Replenishment Inlet – Type W

Nominal Size(mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)
50	293	50	80	202	177




Anti-Syphonage Trap with Branch (Plug or Access Door)

Nominal Size(mm)	H (mm)	L (mm)
50	260	180




Short pipe with Round Door

Nominal Size(mm)	kg/pcs.	H (mm)
50	2.3	190
75	3.1	220
100	5.5	260
150	10.3	330



CAP


Nominal Size(mm)	kg/pcs.	H (mm)
50	0.2	30
75	0.5	35
100	0.7	44
150	1.7	50
200	3.1	56
250	6.0	70
300	9.5	80






YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

Coupling



Type 'B' - SS316 Stainless Steel Coupling

Nominal Size(mm)	H (mm)	L (mm)
50	43	71
75	47	98
100	47	124
150	55	180
200	68	230




Type 'CHA' - SS316 Stainless Steel Coupling

Nominal Size(mm)	H (mm)	L (mm)
50	58	71
75	58	96
100	58	123
150	71	173
200	83	223
250	140	287
300	140	339



YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

Grip Collars / Clamp



Grip Collar / Clamp		
Nominal Size(mm)	H (mm)	L (mm)
75	95	185
100	95	215
150	100	270
200	135	317
250	160	390
300	190	455

CONDITIONS FOR INSTALLATIONS (COUPLING SECURED WITH GRIP COLLAR) :

Grip collars are equipped with little claw like pieces all along the inside. They are available in a variety of different sizes and are commonly using by Epoxy coated pipes which are slippery in nature. Grip collars will prevent pipes and fittings to slide or slip out of place and can ensure both water tightness and mechanical stability of the pipework.

Recommend to use grip collars with couplings :


1. in a pipework at changes of the directions;
2. in the lower part of rainwater collection lines;



YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM

Recommendations On Jointing, Handling ETC.

Recommendation on jointing Method by Mechanical Metal Cooling



Step 1. Take a pipe and cut it to the desired length at right angles to the axis using an electric cutter, following site safety guidelines. Carefully polish the cut end of the pipe and apply epoxy touch-up paint to the cut area as recommended.

Step 2. Slide the coupling (consisting of EPDM gasket inside and stainless steel mounting collar outside) onto the end of the pipe or connection spigot up to the center of the gasket.

Step 3. Push the next pipe or fitting into the coupling, making sure that the cut pipes are square.

Step 4. Tighten the screws of the coupling with a screwdriver, making sure that the electrical contact between the metals is ensured. The pipe can be fixed according to the given sketch and supported b



YU KUNYU BS EN877 EPOXY CAST IRON PIPES & FITTINGS FOR DRAINAGE SYSTEM


Recommendations On Jointing, Handling ETC.

YU Epoxy touch-up paint



YU Epoxy paint is recommended to be applied to the system after pipes have been cut to suit project needs. It is a low-VOC, universal water-based epoxy amine-adduct primer in red color designed for mild to moderate industrial use, for instance, to coat incised surfaces of cast iron pipes.

For best corrosion protection, incised surfaces of cast iron pipes shall be cleaned thoroughly with burrs removed before being coated with '**YU**' epoxy touch-up paint.



Outstanding Feature

- ✓ Easy to use
- ✓ Epoxy Acrylic Resin
- ✓ Reddish Brown
- ✓ Anti-Corrosion